

## Press release

### Diode lasers bars with 2 kW output power for ultra-high power laser applications

**The FBH presented the latest results from their project CryoLaser at CLEO 2015, demonstrating for the first time that a single 1-cm laser bar can deliver at least 2 kilowatt (kW) of optical output power, when cooled to 203 Kelvin.**

Berlin, June 1, 2015

High energy laser applications of the future: these are the target of current diode laser research at the Ferdinand-Braun-Institut, Leibniz-Institut für Höchstfrequenztechnik (FBH). World-wide, teams of scientists and technologists are working on a new generation of ultra-high energy lasers. These are tools for basic science, for novel medical applications and, not least, for laser-induced fusion. Ultra-high power laser systems require diode lasers that are not just extremely capable, but also manufacturable at low costs in very high volumes. Specifically diode lasers bars in the wavelength range 930 to 970 nm are the fundamental building blocks for pump sources for Ytterbium-doped crystals in large laser facilities, where optical pulses are generated with peta-watt class peak energies and picosecond pulse widths. The individual laser bars in these pump sources have a typical output power between 300 and 500 Watts.

The FBH is currently optimizing both the necessary design and technology as a part of the Leibniz project CryoLaser. If the cost per photon is to fall, a higher optical power density must be generated, reducing the amount of material needed. The conversion efficiency must also be dramatically improved for enhanced system efficiency. CryoLaser uses a novel design concept, developing innovative structures that are optimized for operation far below the freezing point (-70°C, 203 K). The performance of diode lasers is substantially improved at these temperatures.

Recently, the FBH team led by Paul Crump presented the latest results from CryoLaser in a talk and a tutorial at CLEO 2015 in San Jose, USA. Building on advances in epitaxial design and packaging technology, FBH bars around 940 nm at temperatures of -70°C (203 K) delivered a world-wide best result of 2 kW peak power per bar at a current of 2 kA, a pulse width of 200 µs and 10 Hz repetition rate, corresponding to a pulse energy of 0.4 J. Peak power was limited by the available current. To date, such powers could only be achieved by combining the optical beams from at least four single bars. Conversion efficiency was 65% at 1 kW output and 56% at 2 kW. Such bars have the potential to play an important role in future high-energy-class laser facilities. Currently, the FBH team is working to further increase the electro-optical conversion efficiency of these bars.

The FBH is responsible for the full value chain within this development project, from design to construction of first prototypes. The final pump sources are being evaluated for potential use in high-energy-class diode-pumped solid-state laser systems together with the world-leading groups in the field.

The related **press picture** and further images are provided on our website: <http://www.fbh-berlin.com/press/download-center>. All images are copyrighted.

#### Further Information on CryoLaser & CLEO

<http://www.fbh-berlin.com/business-areas/diode-lasers/ba-lasers-bars/cryolaser>

## Publications:

C. Frevert, P. Crump, F. Bugge, S. Knigge, A. Ginolas, and G. Erbert "Low-temperature Optimized 940 nm Diode Laser Bars with 1.98 kW Peak Power at 203 K," Paper SM3F.8, Proc. CLEO, San Jose, USA (2015).

P. Crump, C. Frevert, G. Erbert, and G. Tränkle "High Power Diode Lasers for Pumping High Energy Solid State Lasers" Paper SM3M.1 (Tutorial), Proc. CLEO, San Jose, USA (2015).

P. Crump, C. Frevert, A. Ginolas, S. Knigge, A. Maaßdorf, J. Lotz, W. Fassbender, J. Neukum, J. Körner, T. Töpfer, A. Pranovich, M. Divoky, A. Lucianetti, T. Mocek, K. Ertel, M. De Vido, G. Erbert and G. Tränkle, "Joule-Class 940-nm Diode Laser Bars for Millisecond Pulse Applications" IEEE Photon. Technol. Lett., accepted for publication (2015) – joint assessment of previous iterations of high power bars from Cryloaser.

Technical conference and trade show CLEO (10.-15.05.2015) in San Jose, USA:

<http://www.cleoconference.org>

## Contact

Petra Immerz, M.A.  
Communications & Public Relations Manager

Ferdinand-Braun-Institut  
Leibniz-Institut fuer Hoechstfrequenztechnik  
Gustav-Kirchhoff-Str. 4  
12489 Berlin, Germany

phone +49.30.6392-2626  
fax +49.30.6392-2602  
email [petra.immerz@fbh-berlin.de](mailto:petra.immerz@fbh-berlin.de)  
web [www.fbh-berlin.com](http://www.fbh-berlin.com)

## Background information – the FBH

The Ferdinand-Braun-Institut, Leibniz-Institut fuer Hoechstfrequenztechnik (FBH) researches electronic and optical components, modules and systems based on compound semiconductors. These devices are key enablers that address the needs of today's society in fields like communications, energy, health, and mobility. Specifically, FBH develops light sources from the visible to the ultra-violet spectral range: high-power diode lasers with excellent beam quality, UV light sources and hybrid laser systems. Applications range from medical technology, high-precision metrology, and sensors to optical communications in space. In the field of microwaves, FBH develops high-efficiency multi-functional power amplifiers, and millimeter wave frontends targeting energy-efficient mobile communications as well as car safety systems. In addition, compact atmospheric microwave plasma sources that operate with economic low-voltage drivers are fabricated for use in a variety of applications, such as the treatment of skin diseases.

The FBH has a strong international reputation and ensures rapid transfer of technology by working closely with partners in industry and research. The institute has a staff of 290 employees and a budget of 23 million Euros. It is part of the Forschungsverbund Berlin e.V., a member of the Leibniz Association and plays an active role in various networks.

[www.fbh-berlin.com](http://www.fbh-berlin.com)